

CACTUS TECHNOLOGIES 2.5" IDE SSD 503 Series



The Cactus Technologies 2.5" IDE SSD - 503 Series is a high capacity solid-state flash memory product that complies with the IDE interface. Our 2.5" line of robust and reliable storage solutions are designed for today's rigorous industrial market applications. The storage capacity of the Solid State Drive line ranges from 1GB to 64GB.

CACTUS 2.5" IDE SSD FEATURES

- INDUSTRY STANDARD
2.5" IDE SSD FORM FACTOR
- CARD CAPACITIES
 - 1GB to 64GB
- WRITE-ABORT AND BROWN-OUT PROTECTION CIRCUITRY
- INTERFACE SUPPORTS
 - ATA PIO Mode 0-4
 - Multiword DMA Mode 0-2
 - UDMA Mode 0-4
- 5.0V VOLTAGE SUPPORT
- UNIQUE ELECTRONIC SERIAL CARD ID
- TRACEABILITY BARCODE
- SMART LIFE CYCLE ANALYSIS OPTION
- SOLID STATE DESIGN
- INDUSTRY LEADING
 - Data Reliability
 - Shock & Vibration
 - Operating Temp Range
 - Data Transfer Rates
- ZERO DB NOISE
- 4-MILLION HOUR MTBF
- 5-YEAR WARRANTY



PERFORMANCE

Read Data Transfer Rate
up to 50MB/sec
Write Data Transfer Rate
up to 25MB/sec



RELIABILITY

- Advanced Wear Leveling Algorithm
- Error Checking & Correction
- Less Than 1 Error in 10^{14} Bits Read
- MTBF 4,000,000 Hours
- >2,000,000 erase/program cycles



ENVIRONMENTAL & POWER

Operating Temperature Range
Standard 0°C to 70°C
Extended -45°C to +90°C



POWER CONSUMPTION

	5.0V
Read	145mA
Write	100mA
Sleep	15mA



SHOCK & VIBRATION

Shock	3,000G
Vibration	30G peak-to-peak

CACTUS TECHNOLOGIES
2.5" IDE SSD
503 Series



INDUSTRIAL GRADE 2.5" IDE SSD

→ INTERFACE	PC Card ATA, True IDE Mode, and ANSI: ATA7 Compliant	
→ INTERFACE TRANSFER RATE	133MB/sec	
→ POWER REQUIREMENT	DC Input Voltage	3.3V or 5V ± 10%
	Sleep	15mA
	Read	145mA
	Write	100mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	30G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 ¹⁴ bits read
→ CARD CAPACITY	1GB to 64GB	

Cactus Technologies Limited
Suite C, 15/F, Capital Trade Center
62 Tsun Yip Street, Kwun Tong
Kowloon, Hong Kong
Tel: +852-2797-2277
Email: sales@cactus-tech.com

Cactus USA
3112 Windsor Road
Suite A356
Austin, Texas 78703
Tel: (512) 775-0746
Email: americas@cactus-tech.com



www.cactus-tech.com